



[Knowledge Base](#) > [Handsets and Device Provisioning](#) > [Handsets](#) > [Generic SIP configuration for Registration](#)

## Generic SIP configuration for Registration

Mike Johnstone - 2026-03-13 - [Handsets](#)

## Generic SIP configuration for Registration

SIPcity supports most SIP-based VoIP devices including Analog Telephone Adaptors (ATA), IP Phones, IP PBX systems, and Softphones.

SIP Server Name / Proxy Server : **call.sipcity.com.au**

User name / Account ID / Authenticate ID: *(the phone number you are trying to register 61xxxxxxxxx)*

Password: *as set by you*

Transport: TLS port: **5061**

Register with proxy: **yes**

Make calls without registration: **no**

Codecs: **G711a/u, G722, GSM and G729**

|                     |                     |           |
|---------------------|---------------------|-----------|
| <b>Account</b>      | Account1            | ?         |
| Register Status     | Registered          |           |
| Line Active         | Enabled             | ?         |
| Label               | Jazz                | ?         |
| Display Name        | Jazz                | ?         |
| Register Name       | 61289707500         | ?         |
| User Name           | 61289707500         | ?         |
| Password            | ••••••••            | ?         |
| <b>SIP Server 1</b> | ?                   |           |
| Server Host         | call.sipcity.com.au | Port 5061 |
| Transport           | TLS                 | ?         |
| Server Expires      | 180                 | ?         |
| Server Retry Counts | 0                   | ?         |