



[Base de conocimiento](#) > [Troubleshooting](#) > [Yealink Diagnostics 1](#)

Yealink Diagnostics 1

Mike Johnstone - 2024-04-18 - [Troubleshooting](#)

Yealink Diagnostics 1

Yealink provides two diagnostic tools to help our support team diagnose connectivity issues within your network:

1. Local log
2. Syslog which conveniently writes directly back to our network

Local Log 1

Enable Local Log

Local Log Level

Max Log File Size (1024-2048KB)

Export Local Log

Syslog 2

Enable Syslog

Syslog Server Port

Syslog Transport Type

Syslog Level

Syslog Facility

Syslog Prepend MAC

Quick Guide

Step 1: Browse to Phones Web UI

1. Phones web UI: to access the phones web UI press the OK button (on right of the keypad) to retrieve the phones IP address.
2. Enter the IP address in your browser (eg 192.168.1.xx).
3. UserName and Password: Admin- admin, Password- admin.
4. Click Confirm

Step 2: Export Local Log Files

1. Select Settings tab >> Configuration
2. Export System Log: Set the Local log level to 6 -> reboot the phone

3. Pcap Feature: Start to capture the Trace -> reproduce your issue -> stop capturing the Trace -> Export PCAP Trace
4. Export or Import Configuration: Export config.bin
5. Email Download files to our support site.

Step 3: Syslog

1. Select Settings tab >> Configuration
2. Enable Syslog
3. Syslog server: 103.55.116.47 | Port 514
4. Transport Type: UDP
5. Select Confirm